

## 48-port 10G Managed Ring PoE Switch



-  48x 10/100/1000M RJ45 + 4x 10G SFP+
-  L2+ features provide better manageability, security, QoS, and performance
-  Support L2+ Switching features, including VLAN, TRUNK, Mirroring, Port isolation/flow control/speed limit, Storm control, QOS, ACLs etc.
-  Support spanning tree STP and RSTP.
-  Jumbo frames support up to 9.6K kilobytes
-  Support enhanced management through WEB, CLI, TELNET, SNMP
-  Support cable diagnosis
-  48 ports support PoE. Compliant with both IEEE 802.3af and 802.3at. Allow PoE configuration for each PoE port

### Product Description

#### High-performance of both hardware and software

This 10G PoE switch uses top-rated 10G network switching chip, multiple layers PCB design, as well as self-developed switch software system. With combination of hardware and software, it improves product quality from forwarding stability, packet processing speed, and other work capability.

#### Support the fast ring network protocol, free configuration

The switch supports stable and reliable fast Ring Protection Protocol(RSTP). It Achieved real ring loop redundancy protection. Besides, there is no need to configure 10G port when users using this switch, to reduce probability of network failure.

#### Strong network security

Support dynamic or static binding by users' definition, such as IP, MAC, VLAN, PORT, etc. Support port isolation, to prevent communication between two neighbor network equipment within the same broadcast domain , for reducing network risk; Supports perfect storm control function which can suppress broadcast, multi-cast, and uni-cast storm; Support specific ARP inspection which can effectively prevent "ARP spoofing attack" created by hackers or attackers via ARP packets.

#### Convenient management and maintenance

By easy WEB interface(http and https protocol supported), you can conveniently operate and configure all kinds of function in this switch. Support management by CLI, Telnet, Console port, which is more suitable for professional network administrator; It also allow reset by one-press, making maintenance easier.

## 48-port 10G Managed Ring PoE Switch

**Product Specification**

Model	KRN-SW-SM-4840G
Ports	48x 10/100/1000M RJ45 ports
	4x 10G SFP+
Management port	1x Console port
Reset key	1x Reset key, for restore default settings
Bandwidth	184G
Switch throughput	131Mpps @ 64bytes
Operating temperature	-20~+75°C
Input voltage	AC: 110~240V/50~60Hz
Total power consumption	60W

**Technical Characteristic**


Model	KRN-SW-SM-4840G
Protocol & Standard	IEEE 802.3,10BASE-T Ethernet;
	IEEE 802.3u, fast Ethernet Standard;
	IEEE 802.3ab, gigabit Ethernet Standard;
	IEEE 802.3z, gigabit Ethernet Fiber Standard;(AOC fiber cable)
	IEEE 802.3ae,10G Ethernet Standard;
	IEEE 802.3x, full-duplex Ethernet data link layer flow control;
MAC	32K
	supports automatic updates, two-way learning;
SRAM Buffer	32Mb
VLAN	Support up to 4K VLAN;
	Support port-based VLAN;
	Support 802.1Q tag-based VLAN;
Spanning Tree	STP, RSTP, MSTP
Port Aggregation (TRUNK)	Support 4x 10G ports aggregation, support 16x gigabit ports aggregation
	Support 26x groups aggregation
Port Mirroring	Support multiple to single Port mirroring, no limit for quantity of mirroring source ports
Port Isolation	Support downstream ports isolated from each other, while opening communication with upstream ports
Port Flow Control	Support half-duplex back pressure based control;
	Support full-duplex PAUSE frame based control;
Port Speed Limit	Support port-based input/output bandwidth management

## 48-port 10G Managed Ring PoE Switch

Storm Control	Prevents traffic on a LAN from being disrupted by a broadcast, multicast, or unicast storm on a port
	Support port storm threshold setting
Security Features	Hardware support port-based IP+MAC Binding; Hardware support port-based ARP inspection detection;
QOS	SP (Strict Priority);
	WFQ (Weighted Fair Queuing);
	WRR (Weighted Round Robin);
	Head Of Line;
	Best-Effort Service;
	First come first served;
	802.1p;
	Cos/Tos, QOS;
Differentiated Service;	
Network Cable Line Sequence	Support Auto-MDIX, automatic Identification straight-through cable and crossover cable
cable diagnosis	Support cable diagnosis, Cable quality (differential pair impedance 85ohm ~ 125ohm), cable length, a short-circuit line
Negotiation Mode	Support port auto-negotiation function (auto-negotiation transmission rate and duplex mode)
System Maintenance	Support configuration file uploda/download;
	Support update packet upload;
	Support WEB reset;
	Reset by pressing key;
	Support system log save/output;
Network Management	Support WEB management ;
	Support CLI management ;


### 48-port 10G Managed Ring PoE Switch

#### Product Dimension Display



- A. Working LED Indicator
- B. 48x Rj45 Ports
- C. SFP+ Port
- D. Power Input-AC100-240V,50/60Hz

#### Product Application



---

## 48-port 10G Managed Ring PoE Switch

---

### Product Ordering Information

---

**Product Model:** KRN-SW-SM-4840G

**Product Description:** 48-port 10G Managed Ring PoE Switch, 48x 10/100/1000M RJ45 + 4x 10G SFP+, can be set by management system. Total input power is 60W.

**Note:** Default power supply pin type is end-span(1/2+, 3/6-), mid-span(4/5+, 7/8- ) is optional

### Packing List

---

<b>Packing Lists</b>	48-port 10G Managed Ring PoE Switch ( KRN-SW-SM-4840G )
	Power kit
	User Guide
	Warranty Card